





ROLLER FOLLOWERS

STAINLESS STEEL



Type and Part Code

Type	Applicable axis diameter	Feature	Part Code
 RNAST..M (Separable type)	φ 7 ~ φ 60	NAST type without inner ring.	<p>RNAST 15 M R</p> <p>↑ ↑ ↑ ↑</p> <p>Type Bore diameter code</p> <p>Stainless steel R: Crowned outer ring None: Cylindrical outer rings</p>
 NAST..M (Separable type)	φ 6 ~ φ 50	Thick wall outer ring, inner ring. Separable bearing with combined needle roller with precision cage.	<p>NAST 15 M R</p> <p>↑ ↑ ↑ ↑</p> <p>Type Bore diameter code</p> <p>Stainless steel R: Crowned outer ring None: Cylindrical outer rings</p>
 NAST..MZZ (Separable type)	φ 6 ~ φ 50	Separable bearing in which labyrinth seal is formed with combined side plate at both sides of inner ring of NAST type. (NAST-ZZUU type comes with seal)	<p>NAST 15 M ZZ UU R</p> <p>↑ ↑ ↑ ↑ ↑ ↑</p> <p>Type Bore diameter code</p> <p>Stainless steel ZZ: With shield UU: With seal None: With shield</p> <p>R: Crowned outer ring X: Cylindrical outer ring</p>
 NART..MR (Non-separable type)	φ 5 ~ φ 50	Non-separable bearing with fixed side plate at inner ring. Mitigate eccentric load with spherical shape at outer diameter of outer ring (code R). (NART-UUR type comes with seal)	<p>NART 15 M UU V R</p> <p>↑ ↑ ↑ ↑ ↑ ↑</p> <p>Type Bore diameter code</p> <p>Stainless steel UU: With seal V: Full complement None: With shield</p> <p>R: Crowned outer ring X: Cylindrical outer ring</p>